

Technical data for MiniSteam E (electrodes)

Type	MSE05		MSE10
Steam output [kg/h]	4.4 - 4.8	4.8 - 5.2	9.5 - 10.4
Electrical connection ⁽¹⁾ [V/Hz]	220-240/1/N/50-60	380-415/3/N/50-60	
Electrical power [kW]	3.3 - 3.6	3.6 - 3.9	7.1 - 7.8
Rated current [A]	15.0	5.4	10.8
Fuse [A]	1 x 16	3 x 10	3 x 16
Control voltage (internal) [V]	220-240V/1/N		
Weight (empty) [kg]	15		
Weight (operating) [kg]	20		
Dimensions WxHxD ⁽⁵⁾ [mm]	595 x 390 x 255		
Water supply	1 to 10 bar (100 x 10 ³ to 1000 x 10 ³ Pa), for 3/4" external thread		
Waste water connection [mm]	in on-site drain		

Subject to technical changes.

⁽¹⁾ Other voltages upon request.

⁽⁵⁾ Outer width and depth dimensions.
Height including drain connection.

Our service for you

- HygroMatik distributors in more than 45 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planning tools and workshop offers are available online at www.hygromatik.com



HYGROMATIK
WE HUMIDIFY THE AIR

HygroMatik GmbH
Lise-Meitner-Str. 3
24558 Henstedt-Ulzburg
Germany

T +49 4193 895-0
F +49 4193 895-33
hy@hygromatik.de
www.hygromatik.com