

## Technical Data LPS

Type		45	72	110
Power rating	[kW]	0.15	0.16	0.18
Water capacity (16 bar)	[l/h]	4 – 56	10 - 90	20 – 130
Current connection	[A]	1.9	2.1	2.7
Voltage connection	[V/ph/Hz]	230/1/50		
Control signal *	[V/mA]	0 – 10 / 4 – 20		
Dimensions Vortex modules	[mm]	150 x 150		
Number of nozzles		15	22	32
Absorption distance (optimum)	[m]	0.9		
Overall installation length, min.	[m]	1.5		
Flow rate	[m/s]	0.9 – 2.8		
Pressure drop in duct	[Pa]	80 at 2.0 m/s air velocity		

\* Other control signals on request  
Subject to technical amendments without notice

## Our Service for you

- HygroMatik distributors in more than 35 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planing tools and workshop offers are available online at [www.hygromatik.com](http://www.hygromatik.com)



**HYGROMATIK**<sup>®</sup>  
WE HUMIDIFY THE AIR

HygroMatik GmbH      T +49 4193 895-0  
Lise-Meitner-Str. 3      F +49 4193 895-33  
24558 Henstedt-Ulzburg      hy@hygromatik.de  
Germany      www.hygromatik.com

A Member of the **spirax** / **sarco** group